



DIRECT GASKETS LIMITED
UNIT 2. LEE SMITH STREET
HEDON ROAD
HULL
HU9 1SD



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

BLUE GARD 3700

DESCRIPTION

Blue Gard 3700 is light grey in colour.

SERVICE

Water and mild chemicals.

Max recommended temperatures : -73°C to +205°C

Max recommended temperature: SHORT TERM +371°C

Max recommended pressure : 83 BAR / 1200 PSI

These temperature and pressure guides cannot necessarily be used simultaneously and may not apply to all thicknesses.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION



DIRECT GASKETS LIMITED
 UNIT 2. LEE SMITH STREET
 HEDON ROAD
 HULL
 HU9 1SD



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
 FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

TYPICAL PROPERTIES BLUE GARD 3700

Tensile Strength	Across Grain ASTM F152	2500 psi / 17 N/mm ²
Compression	ASTM F36	7-17%
Recovery	ASTM F36	40%
Creep Relaxation	ASTM F38	25%
Density	ASTM F1315	100 lbs/ft ³ / 1.60 grams/cm ³

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION