



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

CLEAR POLY

| | |
|---|--|
| <u>COLOUR:</u> | Clear |
| <u>SHORE HARDNESS:</u> | 75° +/- 5 |
| <u>TENSILE STRENGTH:</u> | 10 MPa |
| <u>ELONGATION AT BREAK (%):</u> | 150 |
| <u>SPECIFIC GRAVITY:</u> | 1.70 +/- 0.05 |
| <u>ABRASION RESISTANCE (mm³):</u> | 150 |
| <u>RECOMMENDED TEMP:</u> | -20°C to +100°C |
| <u>GENERAL PROPERTIES:</u> | High Abrasion |
| <u>SURFACE FINISH:</u> | Plate/Plate |
| <u>THICKNESS RANGE:</u> | 2mm, 3mm & 4mm |
| <u>ROLL SIZE:</u> | LENGTH - up to 10 metres (subject to thickness) WIDTH - up to 1.2 metres (subject to thickness) |
| <u>TOLERANCE - ROLL SIZE:</u> | +/- 2.5% |

THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION