

DIRECT GASKETS LIMITED UNITS 26 - 36 DANSOM LANE SOUTH HULL HU8 7LA





TELEPHONE: 01482 219655EMAIL: info@direct-gaskets.co.ukFAX: 01482 321162WEBSITE: www.direct-gaskets.co.uk

## FINE RIBBED MATTING

COLOUR:	Black
SHORE HARDNESS:	65-70° +/- 5
TENSILE STRENGTH:	2.5 MPa
SPECIFIC GRAVITY:	1.5 +/- 0.05
<b>RECOMMENDED TEMP:</b>	-30°C to +70°C
<b>GENERAL PROPERTIES:</b>	Air & Water Resistant
	High Abrasion & Non-Slip
SURFACE FINISH:	Ribbed Matting
THICKNESS RANGE:	3mm, 4.5mm & 6mm
ROLL SIZE:	LENGTH - up to 10 metres
	WIDTH - up to 1.2 metres (subject to thickness)
TOLERANCE - ROLL SIZE:	+/- 2.5%

## THIS INFORMATION IS FOR A GENERAL GUIDE ONLY. FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION