



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

GLASS LADDER TAPE

DESCRIPTION

Woven tape which is produced from texturized yarns which give good insulation values. The ladder section is created by omitting warp threads, by doing this it enables bolts or screws to penetrate the material without weakening the structure.

FINISHED FABRIC

COLOUR: Untreated white glass fibres

WEIGHT: 1200 g/m²

THICKNESS: 3mm & 5mm

RECOMMENDED TEMP: +550°C (Melting Point 800°C)

ROLL SIZE: LENGTH - 30 metres

WIDTH - 25mm - 150mm

TOLERANCE: +/- 5%

BASE FABRIC CINSTRUCTION

WEAVE PATTERN: Plain x 2ply

CONSTRUCTION: Warp: 8.0 per cm

Weft: 3.0 per cm

YARN COUNT: Warp: ET9 1000 Tex

Weft: ET9 660 Tex

TOLERANCE: +/-5%

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION