



DIRECT GASKETS LIMITED  
UNITS 26 - 36  
DANSOM LANE SOUTH  
HULL  
HU8 7LA



TELEPHONE: 01482 219655  
FAX: 01482 321162

EMAIL: [info@direct-gaskets.co.uk](mailto:info@direct-gaskets.co.uk)  
WEBSITE: [www.direct-gaskets.co.uk](http://www.direct-gaskets.co.uk)

## SBR INSERTION

|  |  |
|--|--|
| <b><u>COLOUR:</u></b>                  | Black  |
| <b><u>SHORE HARDNESS:</u></b>          | 70° +/- 5  |
| <b><u>TENSILE STRENGTH:</u></b>        | 3 MPa = 30 Bar/435 PSI   |
| <b><u>INSERTION:</u></b>               | Cloth  |
| <b><u>ELONGATION AT BREAK (%):</u></b> | 150  |
| <b><u>SPECIFIC GRAVITY:</u></b>        | 1.5 +/- 0.05   |
| <b><u>RECOMMENDED TEMP:</u></b>        | -20°C to +70°C   |
| <b><u>GENERAL PROPERTIES:</u></b>      | Air & Water Resistant<br>Single PLY  |
| <b><u>SURFACE FINISH:</u></b>          | Plate/Plate  |
| <b><u>THICKNESS RANGE:</u></b>         | 1.5mm - 10mm   |
| <b><u>ROLL SIZE:</u></b>               | LENGTH - up to 20 metres (subject to thickness)<br>WIDTH - up to 1.4 metres (subject to thickness) |
| <b><u>TOLERANCE - ROLL SIZE:</u></b>   | +/- 2.5%   |

**THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.**

**FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.**

**ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION**