



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

NITRILE

<u>COLOUR:</u>	Black
<u>SHORE HARDNESS:</u>	70° +/- 5
<u>TENSILE STRENGTH:</u>	4 MPa = 40 Bar/580 PSI
<u>ELONGATION AT BREAK (%):</u>	300
<u>SPECIFIC GRAVITY:</u>	1.45 +/- 0.05
<u>RECOMMENDED TEMP:</u>	-20°C to +120°C
<u>GENERAL PROPERTIES:</u>	Oil & Heat Resistant
<u>SURFACE FINISH:</u>	Plate/Plate
<u>THICKNESS RANGE:</u>	0.5mm - 20mm
<u>ROLL SIZE:</u>	LENGTH - up to 20 metres (subject to thickness) WIDTH - up to 1.4 metres (subject to thickness)
<u>TOLERANCE - ROLL SIZE:</u>	+/- 2.5%

THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION