



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

NITRILE/NEOPRENE BONDED CORK

<u>COLOUR:</u>	Brown
<u>SHORE HARDNESS:</u>	55° +/- 5
<u>TENSILE STRENGTH:</u>	11 MPa
<u>ELONGATION AT BREAK (%):</u>	N/A
<u>SPECIFIC GRAVITY:</u>	0.48 +/- 0.05
<u>RECOMMENDED TEMP:</u>	-30°C to +120°C
<u>GENERAL PROPERTIES:</u>	Nitrile & Neoprene Bonded Oil, Chemical, Air & Water Resistant
<u>SURFACE FINISH:</u>	Natural
<u>THICKNESS RANGE:</u>	1mm - 6mm
<u>ROLL SIZE:</u>	LENGTH - up to 20 metres (subject to thickness) WIDTH - up to 1 metre
<u>TOLERANCE - ROLL SIZE:</u>	+/- 2.5%

THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION