



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

PLASTIC SHIM B - 0.015" (0.038mm) to 0.125" (3mm)

<u>COLOUR:</u>	Various	
<u>TENSILE STRENGTH:</u>	3560 lbf/in ²	(BS 2782 301 G)
<u>ULTIMATE COMPRESSIVE STRENGTH:</u>	4000-8000psi	(BS 2782 301 G)
<u>SPECIFIC GRAVITY:</u>	0.91-0.95	
<u>WATER ABSORPTION:</u>	0.3 MG (<0.02%)	(BS 2782 502D)
<u>RECOMMENDED TEMP:</u>	-70°C to +130°C	
<u>SOFTENING POINT:</u>	144°C (BS 2782 102D)	
<u>GENERAL PROPERTIES:</u>	Oil, Grease & Solvent Resistant	
	Low Water Absorption	
<u>SURFACE FINISH:</u>	Plate/Plate	
<u>THICKNESS RANGE:</u>	0.038mm - 3mm	
<u>ROLL SIZE:</u>	1200mm x 610mm sheets	
<u>TOLERANCE - ROLL SIZE:</u>	+/- 2.5%	

THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION