



DIRECT GASKETS LIMITED
UNIT 2. LEE SMITH STREET
HEDON ROAD
HULL
HU9 1SD



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

PW900 SIDE CURTAIN

<u>COLOUR:</u>	Range
<u>FABRIC:</u>	100% PES 1100 d/tex 12 x 12 threads/cm
<u>WEIGHT:</u>	900 g/m ² (DIN EN ISO 2286-2)
<u>BREAKING STRENGTH:</u>	Warp 4000 N/5cm (EN ISO 1421-1) Weft 4000 N/cm
<u>TEAR STRENGTH:</u>	Warp 600 N (DIN53 363) Weft 500 N (DIN53 363)
<u>COATING ADHESION:</u>	100 N/5cm (EN ISO 2411)
<u>TEMPERATURE RESISTANCE:</u>	-30°C to +70°C (DIN EN 1876-2)
<u>FIRE BEHAVIOUR:</u>	<100mm/min (ISO 3795)
<u>SURFACE FINISH:</u>	Gloss & Lacquered
<u>ROLL SIZE:</u>	WIDTH 300cm (3000mm)

THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION