



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

TOPOG-E

DESCRIPTION

Rubber joint designed for quick and easy installation. Simple to remove and come in many sizes.

SERVICE

For use in: steam pressure vessels, hot water heaters, water purifiers and tanks. Good resistance to: alcohols, silicone oils and greases, dilute acids, salts and ammonia.

Max recommended temperature : OPERATING STEAM 193°C

Max recommended pressure : 12 BAR / 180 PSI

These temperature and pressure guides cannot necessarily be used simultaneously.

EXPECTED SERVICE

Continuous operating steam pressure in PSI & BAR	Approximate maximum service in Months
Below 25 PSI (2BAR)	18-24
25-100 PSI (2-7 BAR)	12-18
100-180 PSI (7-12 BAR)	12-15
180-200 PSI (12-14 BAR)	10-12
200-225 PSI (14-16 BAR)	8-10
225-250 PSI (16-17 BAR)	6-8

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION