



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

VF225 - GREASY GLAND PACKING

SERVICE CAPABILITY

PRESSURE RATING : 50 BAR
TEMPERATURE : up to +120°C
ROTARY SPEED : 8 metres per second
pH RANGE : 5 - 9

PRODUCT INFORMATION

VF225 is square-braided from long, heavy duty natural fibre yarns.

These high-strength yarns are thoroughly impregnated, before and after braiding, with a specially blended lubricant.

The packing is designed to give very low coefficient of friction resistance to wear and rotting, good compressibility, high flexibility, high tensile strength and ease of installation.

VF225 is an excellent, general purpose packing especially for water duties. Its resilience, low shaft wear, ease of fitting and economic cost makes VF225 an effective choice for many standard applications.

APPLICATIONS

VF225 is suitable for all general water-based applications in pumps and valves, up to 120°C.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION