



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

VF4 - PTFE/FLAX GLAND PACKING

SERVICE CAPABILITY

PRESSURE RATING	: 130 BAR
TEMPERATURE	: -30 up to +120°C
ROTARY SPEED	: 10 metres per second
pH RANGE	: 2 - 12

PRODUCT INFORMATION

VF4 is braided from selected, long fibre, heavy duty, flax yarns thoroughly impregnated yarn by yarn with PTFE and treated with break-in lubricants.

The packing is designed to give a very low coefficient of friction, resistance to wear and rotting, good compressibility, high flexibility, high tensile strength and comparative ease of installation and take-up especially on large cross-sections.

VF4 PTFE/FLAX packing is especially designed to seal large cross-sectional areas and is ideal to solve the exacting sealing requirements of stern glands in the marine field. The packing will also be of superior service in heavy reciprocating machinery, rotary applications handling abrasive media and heavy duty static applications, such as tank lid seals.

APPLICATIONS

For use in paper, marine, chemical, pharmaceutical, sugar and water industries against salt water, slurries, hydrocarbons, oils. Greases and solvents.

Hydraulic presses and accumulator tanks.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION