



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655
FAX: 01482 321162

EMAIL: info@direct-gaskets.co.uk
WEBSITE: www.direct-gaskets.co.uk

VG1D - GRAPHITED GLASS GLAND PACKING

SERVICE CAPABILITY

PRESSURE RATING : 250 BAR
TEMPERATURE : -100°C up to +550°C
ROTARY SPEED : 1 metres per second
pH RANGE : 4 - 11

PRODUCT INFORMATION

VG1D is square braided from continuous filament, texturized Glass fibres which is re-inforced with Inconel wire and impregnated yarn by yarn with pure Graphite powder and a corrosion inhibitor.

VG1D Graphited Glass packing is designed as a substitute to classic Asbestos packings with high temperature capability. The addition of the Inconel wire reinforcements results in a true high pressure and high temperature traditional valve packing that had the advantage of being non-Asbestos.

APPLICATIONS

General purpose, non-Asbestos valve packing against steam, water, oils, air, alkalis, mild acids and chemicals. Not suitable for very arduous conditions.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION