



DIRECT GASKETS LIMITED
UNITS 26 - 36
DANSOM LANE SOUTH
HULL
HU8 7LA



TELEPHONE: 01482 219655 EMAIL: info@direct-gaskets.co.uk
FAX: 01482 321162 WEBSITE: www.direct-gaskets.co.uk

VT8 - PTFE VALVE SEAL STEAM PACKING

SERVICE CAPABILITY

PRESSURE RATING : 150 BAR
TEMPERATURE : -100°C up to +260°C
ROTARY SPEED : 1 metres per second
pH RANGE : 0 - 14

PRODUCT INFORMATION

VT8 is supplied as a double construction of a 100% unscintered PTFE core with a spiral covering of PTFE tape. VT8 provides the versatility of an extruded malleable core with the additional strength and extrusion resistance of the PTFE tape covering.

The result is a low friction, extrusion resistant, Teflon packing with near universal chemical resistance.

VT8 will not harden nor shrink in application and provides an instant packing and instant gasket on one very economical spool. In valves, wrap VT8 round the stem to fill the gland (no need for cut rings), tighten the gland follower and the PTFE moulds to form a tight leak free seal. VT8 is guaranteed to last the life of the valve to which it is fitted.

APPLICATIONS

Universal PTFE sealing material for gasketing and life-long valve packing. For practically all chemicals. Not suitable for liquid or gaseous oxygen.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION