

DIRECT GASKETS LIMITED UNITS 26 - 36 DANSOM LANE SOUTH HULL HU8 7LA



TELEPHONE: 01482 219655

EMAIL: info@direct-gaskets.co.uk

FAX: 01482 321162 WE

WEBSITE: www.direct-gaskets.co.uk

VT9L - PTFE GLAND PACKING

SERVICE CAPABILITY

PRESSURE RATING : 120 BAR

TEMPERATURE : -40°c up to +280°C ROTARY SPEED : 12 metres per second

pH RANGE : 0 - 14

PRODUCT INFORMATION

VT9L is braided from pure PTFE fibres, in the form of multi-filament yarns, vacuum impregnated with PTFE dispersion and saturated with chemically resistant lubricants.

The PTFE fibres are pre-shrunk and square inter-braided to produce a dimensionally stable packing.

VT9L chemical pump packing exhibits high mechanical strength and high operational stability under demanding operation conditions, in addition to excellent non-friction characteristics.

Shaft wear is virtually eliminated and VT9L is capable of performing in service conditions far beyond conventional packings.

APPLICATIONS

For use against solvents and virtually all chemicals with exceptions of molten and alkali metals and fluorine.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION