

DIRECT GASKETS LIMITED UNITS 26 - 36 DANSOM LANE SOUTH HULL HU8 7LA





TELEPHONE: 01482 219655 FAX: 01482 321162 W

EMAIL: info@direct-gaskets.co.uk WEBSITE: www.direct-gaskets.co.uk

## WHITE SILICONE

COLOUR:	White
SHORE HARDNESS:	60° +/- 5
TENSILE STRENGTH:	6 MPa = 55 Bar/800 PSI
ELONGATION AT BREAK (%):	300
SPECIFIC GRAVITY:	1.20 +/- 0.05
<b>RECOMMENDED TEMP:</b>	-90°C to +200°C
<b>GENERAL PROPERTIES:</b>	Flame Retardant
	UV Stable, WRAS Approved & FDA Approved
SURFACE FINISH:	Plate/Plate
THICKNESS RANGE:	1.5mm - 10mm
ROLL SIZE:	LENGTH - up to 10 metres (subject to thickness)
	WIDTH - up to 1.2 metres (subject to thickness)
TOLERANCE - ROLL SIZE:	+/- 2.5%

## THIS INFORMATION IS FOR A GENERAL GUIDE ONLY.

## FURTHER TECHNICAL INFORMATION IS AVAILABLE ON REQUEST.

ALL PRESSURES AND TEMPERATURES ARE SUBJECT TO INDIVIDUAL APPLICATION